

Standard Tools for Preparing the Panels & Installing the Panels

Circular Saw

Brand: Makita, Bosch, Festool, Skil, etc.

Remarks:

- Any model that could fit the EQUITONE fibre cement saw blade (cordless or electric version).
- It is encouraged that the circular saw comes with a dust extraction system.
- It is encouraged to use the circular saw with a guide rail.



Dust Extraction System

Guide Rail



Cordless Drill

Brand: Makita, Bosch, Festool, Skil, etc.

Remarks:

- Any model that could fit the EQUITONE drill bit.



Rivet Gun

Brand: Gesipa, Patta, Heracles, etc.

Remarks:

- Most models come with standard nose pieces/nozzle to fit common rivet sizes.
- For pneumatic rivet guns, an air compressor with at least 2.5 HP is required.



Air Compressor



Spacers

Remarks:

- The material can be either made from plastic, timber, fibre cement, etc.
- The thickness is the same as the required joint size (minimum 8mm; maximum 12mm; 10mm preferred).



Sandpaper

Remarks:

- 80 grit sandpaper is used to remove the burrs at the edges of the panel after cutting



Standard Tools for Rivet Removal

Angle Grinder

- Brand: Makita, Bosch, etc. (cordless or electric version).

Remarks: Please equip machine with a suitable cutting wheel that can cut metals.



Rubber Mallet



Pin Punch



8mm diameter HSS Drill Bit



EQUITONE Special Accessories

Fibre Cement Saw Blade

Brand: Leitz Diamaster Pro.

Remarks:

- Blade specification:

Blade diameter	Blade thickness	Borehole	Number of teeth	Saw speed
160mm	3.2mm	20mm	4	4,000rpm
190mm	3.2mm	20mm	4	3,200rpm
225mm	3.2mm	30mm	6	2,800rpm
300mm	3.2mm	30mm	8	2,000rpm

- Please check the blade's suitability with the circular saw.
- Each blade can last up to 5000m of linear cutting.




Jigsaw Blade

Brand: Bosch T141HM.

Remarks:

- This is used for on-site curve cutting.
- Turn off pendulum function of Jigsaw when cutting.



TOOLS & ACCESSORIES - RIVET FIXING

Drill Bit

Brand: Guhring

Remarks:

- 11mm diameter.
- Solid carbide material.



Centralising Tool

Remarks:

- Equipped with 4.1mm drill bit or 4.9mm drill bit (for mineralis).



Rivet Setting Tool

Remarks:

- Fixed to nozzle of rivet gun.
- To be used when fixing UNI-Rivets.
- Makes sure that the rivet gun is perpendicular to the panel.
- Protects the head of the rivet from scratches.



Foam Tape

Remarks:

- Single sided adhesive.
- Material can be either PVC, EPDM, etc.
- Medium density preferred.
- Thickness must be thicker than 2mm.



Luko

Remarks:

- Used to reseal cut edges of EQUITONE [natura] & [natura pro].
- Can be purchased with applicator set.
- Has 1 year shelf life.



For further information, please consult with EQUITONE Asia Pacific Technical Department.

EQUITONE Asia Pacific

www.equitone.com

info.asia@equitone.com

info.australia@equitone.com